





Schweißfittings

4

Rohrabmessungen				
NW (mm)	Zoll	DIN 11850-R2 Außen-Ø (mm)	ISO Außen-Ø (mm)	metrische Abmessung (mm)
10	3/8"	13	17,2	12 x 1,0
15	1/2"	19	21,3	18 x 1,5
20	3/4"	23	26,9	23 x 1,5
25	1"	29	33,7	28 x 1,5
32	1 1/4"	35	42,4	35 x 1,5
40	1 1/2"	41	48,3	43 x 1,5
50	2"	53	60,3	54 x 2,0
65	2 1/2"	70	76,1	69 x 2,0
80	3"	85	88,9	84 x 2,0
100	4"	104	114,3	104 x 2,0
125	5"	129	139,7	129 x 2,0
150	6"	154	168,3	154 x 2,0
200	8"	204	219,1	204 x 2,0
250	10"		273,0	254 x 2,0
300	12"		323,9	304 x 2,0
350	14"		355,6	354 x 2,0
400	16"		406,4	406 x 3,0
450	18"		457,2	
500	20"		508,0	
600	24"		609,6	
700	28"		711,2	
800	32"		812,8	
900	36"		914,4	
1000	40"		1016,0	

T-Stücke mit gleichem Abgang EN 10253 Typ A (DIN 2615)

Typ 1.4571* 	Typ 1.4541 	Typ 1.4571* 	Typ 1.4541 	Typ P235GH-TC1 Stahl schwarz	Anschluss D x S	α
geschweißte Ausführung				nahtlose Ausführung		
T1215GA6**	---	---	---	---	12,0 x 1,5	26
---	---	T17,223A6	---	---	17,0 x 2,3	20
T1815GA6**	---	---	---	---	18,0 x 1,5	35
T21,320GA6	T21,320GA4	T21,320A6	T21,320A4	T21,320ST	21,3 x 2,0	25
---	---	T21,329A6	T21,329A4	---	x 2,9	
T26,920GA6	T26,920GA4	T26,920A6	---	---	26,9 x 2,0	29
---	---	T26,923A6	T26,923A4	T26,923ST	x 2,3	
---	---	T26,929A6	T26,929A4	---	x 2,9	
T33,720GA6	T33,720GA4	T33,720A6	T33,720A4	---	33,7 x 2,0	38
T33,726GA6	T33,726GA4	T33,726A6	T33,726A4	T33,726ST	x 2,6	
T42,420GA6	T42,420GA4	T42,420A6	T42,420A4	---	42,4 x 2,0	48
T42,426GA6	T42,426GA4	T42,426A6	T42,426A4	T42,426ST	x 2,6	
---	---	T42,429A6	T42,429A4	---	x 2,9	
T48,320GA6	T48,320GA4	T48,320A6	T48,320A4	---	48,3 x 2,0	57
T48,326GA6	T48,326GA4	T48,326A6	T48,326A4	T48,326ST	x 2,6	
---	---	T48,329A6	T48,329A4	---	x 2,9	
---	---	T48,336A6	T48,336A4	---	x 3,6	
T60,320GA6	T60,320GA4	T60,320A6	T60,320A4	---	60,3 x 2,0	64
T60,326GA6	T60,326GA4	---	---	---	x 2,6	
T60,329GA6	T60,329GA4	T60,329A6	T60,329A4	T60,329ST	x 2,9	
T76,123GA6	T76,123GA4	---	---	---	76,1 x 2,3	76
T76,125GA6	T76,125GA4	---	---	---	x 2,5	
T76,129GA6	T76,129GA4	T76,129A6	T76,129A4	T76,129ST	x 2,9	
T88,923GA6	T88,923GA4	---	---	---	88,9 x 2,3	86
T88,925GA6	T88,925GA4	---	---	---	x 2,5	
T88,930GA6	T88,930GA4	---	---	---	x 3,0	
---	---	T88,932A6	T88,932A4	T88,932ST	x 3,2	
T114,326GA6	T114,326GA4	---	---	---	114,3 x 2,6	105
T114,330GA6	T114,330GA4	---	---	---	x 3,0	
---	---	T114,336A6	T114,336A4	T114,336ST	x 3,6	
T139,726GA6	T139,726GA4	---	---	---	139,7 x 2,6	124
T139,730GA6	T139,730GA4	---	---	---	x 3,0	
---	---	T139,740A6	T139,740A4	T139,740ST	x 4,0	
T168,326GA6	T168,326GA4	---	---	---	168,3 x 2,6	143
T168,330GA6	T168,330GA4	---	---	---	x 3,0	
---	---	T168,345A6	T168,345A4	T168,345ST	x 4,5	
T219,130GA6	T219,130GA4	---	---	---	219,1 x 3,0	178
---	---	T219,163A6	T219,163A4	T219,163ST	x 6,3	

* Standardlieferprogramm, ** DIN 11852/1.4404



 Rostfrei

