

Kompaktzylinder UNITOP

Hauptabmessungen - Kompaktzylinder SES/SESBS

UNITOP (Eco-Line)

Ø 12 - 25

Ø 32 - 63

Option -B

Kolben Ø	A	B	C	D	E	F	H	J	K	L	M	N	O	P	Q	R	S
12 mm	42,5	38,0	8	6	29	7	M 3	30,0	5	4,5	18	M 4	6	M 5	16	14	M 6
16 mm	42,5	38,0	10	8	29	7	M 4	30,0	6	4,5	18	M 4	6	M 5	20	18	M 8
20 mm	42,5	38,0	12	10	36	7	M 5	37,5	8	4,5	22	M 5	6	M 5	22	20	M 10 x 1,25
25 mm	45,0	39,5	12	10	40	7	M 5	41,5	8	5,5	26	M 5	6	M 5	22	20	M 10 x 1,25
32 mm	50,5	44,5	14	12	50	8	M 6	52,0	10	6,0	32	M 6	6	G 1/8"	22	20	M 10 x 1,25
40 mm	52,0	45,5	14	12	60	8	M 6	62,5	10	6,5	42	M 6	6	G 1/8"	22	20	M 10 x 1,25
50 mm	53,0	45,5	16	16	68	8	M 8	71,0	13	7,5	50	M 8	6	G 1/8"	24	22	M 12 x 1,25
63 mm	57,5	50,0	16	16	87	8	M 8	91,0	13	7,5	62	M 10	8	G 1/8"	24	22	M 12 x 1,25

Hauptabmessungen - Kompaktzylinder NXD/NXE

UNITOP

Ø 12 - 25

Ø 32 - 100

Option -AG

Kolben Ø	A	Ø B	Ø C	Ø D	E	Ø F	G1	G2	J ¹⁾	L	M	N	O	P	Q	T	U	V	Z
12 mm	29	6	6	3,3	M 4	6,0	M 3	M 6	38,0	0	M 5	8,0	12,25	18	6	5	3,5	16	4,5
16 mm	29	8	6	3,3	M 4	6,0	M 4	M 8	38,0	0	M 5	8,0	12,25	18	8	6	3,5	20	4,5
20 mm	36	10	6	4,2	M 5	7,5	M 5	M 10 x 1,25	38,0	0	M 5	8,0	12,25	22	10	8	4,5	22	4,5
25 mm	40	10	6	4,2	M 5	7,5	M 5	M 10 x 1,25	39,5	0	M 5	8,0	12,75	26	10	8	4,5	22	5,5
32 mm	50	12	6	5,2	M 6	9,0	M 6	M 10 x 1,25	44,5	4	G 1/8"	8,0	14,50	32	12	10	5,5	22	6,0
40 mm	58	12	6	5,2	M 6	9,0	M 6	M 10 x 1,25	45,5	3	G 1/8"	8,0	14,75	42	12	10	5,5	22	6,5
50 mm	67	16	6	6,7	M 8	10,5	M 8	M 12 x 1,25	45,5	0	G 1/8"	8,0	14,75	50	12	13	6,5	24	7,5
63 mm	80	16	8	8,5	M 10	13,5	M 8	M 12 x 1,25	50,0	0	G 1/8"	8,0	14,25	62	14	13	8,5	24	7,5
80 mm	100	20	8	8,5	M 10	13,5	M 10	M 16 x 1,5	56,0	0	G 1/8"	8,5	16,00	82	15	17	8,5	32	8,0
100 mm	124	25	8	8,5	M 10	13,5	M 12	M 20 x 1,5	66,5	0	G 1/4"	10,5	19,25	103	20	22	8,5	40	10,0

¹⁾ für NXE mit Hub > 25 mm bitte anfragen.